

**Transmittance** **$U_w \geq 0.88$  (W/m<sup>2</sup>K)**

Consult typology, dimensions and glass.

**Acoustic insulation**Maximum glazing **44 mm**Minimum glazing **28 mm**Maximum acoustic insulation **Rw = 43 dB****Sightlines**

Frame 160 mm / 3 rail 248 mm / 4 rail 336 mm

Lateral sightline 62 mm

Interlock 25 mm

**Maximum sash dimensions**

Width (L) = 3,500 mm

Height (H) = 3,500 mm

Consult maximum dimensions according to typologies.

**Maximum sash weight** **500 kg**

Consult maximum weight according to typologies.

**Categories achieved at test centre**

Protection against atmospheric agents.

**Air permeability****(UNE-EN 12207): Class 4****Watertightness****(UNE-EN 12208): Class E900****Wind resistance****(UNE-EN 12210): Class C5**

Reference test 4.00 x 3.038 m / 2 sashes

Test verified by

**ALUMINIOS CORTIZO S.A.U.****Extrusion alloy****6063 T-5****Finishes**

Possibility of dual colour.

Colour powder coating (RAL, mottled &amp; rough).

According to Qualicoat &gt;60 microns

**Wood effect powder coating.**

According to Qualideco standard

**Anodising.**

According to Ewwa Euras / Standard Class 15 / Optionally Class 20 and 25

**Opening possibilities**

Sliding

Possibility of 1, 2, 3 and 4 rails

Possibility of inner and outer corner sash at 90° without mullion

Pocket sliding door

