

Transmittance**U_{cw} ≥ 0.6** (W/m²K)

Consult typology, dimensions and glass.

GlazingMax. 64 mm
Min. 4 mm**Inner sightlines**52 mm mullion
52 mm transom**Profile Thickness**2.1 & 3.0 mm mullion
2.1 mm transom**Thermal Break**6, 12 & 30 mm
stackable profiles**EPDM Gaskets**

Totally vulcanised corner gasket

Maximum dimensions / Sash**Hidden Top Hung**Width (L) 2,500 - 500 mm
Height (H) 2,500 - 650 mm**Hidden Side Hung / Tilt & Turn**Width (L) 1,400 - 500 mm
Height (H) 1,900 - 600 mm**Parallel opening**Width (L) 1,500 - 450 mm
Height (H) 3,000 - 650 mm**Maximum weight / Sash**

Hidden top hung opening	180 Kg
Hidden parallel opening	200 Kg
Hidden Tilt & turn / Side hung opening	100 Kg
Fixed lights	750 Kg

Certificates

CWCT British Certification

**Categories achieved at test centre**

Protection against atmospheric agents.

Air permeability**(UNE-EN 12152):** Class AE**Water tightness****(UNE-EN 12254):** Class RE1500**Wind resistance****(UNE-EN 13116):** Passed

Design loading 2,400 Pa - Security loading 3,000 Pa

Reference test 3.00 x 3.50 m.

Test verified by

ALUMINIOS CORTIZO S.A.U.**Extrusion alloy**

6063 T-6

Finishes

Colour powder coating (RAL, mottled & rough).

According to Qualicoat >60 microns

Wood effect powder coating.

According to Qualideco standard

Anodised.

According to Ewwa Euras / Standard Class 15 / Optionally Class 20 and 25

Opening possibilities

Hidden top hung

Hidden parallel opening

Hidden side hung / tilt & turn

Options for covers

85 mm deep elliptical cover

34 mm deep H shape cover

14, 19, 100 & 145 mm deep rectangular cover

Flat cover

155 mm deep pyramidal cover

